LINCOLNSHIRE LIME

Leading suppliers of specialist
building materials

CONSERVATION FILLER

Lincolnshire Lime conservation filler contains no plastics, resins or synthetic material - it is made purely from lime putty and chalk, creating a highly breathable filler which won't show through limewash.
Unlike common fillers, it reflects the same frequency of light as the material it is applied to, meaning it produces no 'shine through' or 'flashing'. This is a revolutionary product which is proving to be extremely popular, and for peace of mind, our conservation filler is made with only natural elements.

Lime Putty
CAS No. 1305-62-0
EINECS No. 215-137-3
Precautionary Statements
P102 Keep out of reach of children
P280 Wear protective gloves, eye protection/ face protection.
P305 + P351 + P310 If in eyes rinse cautiously with water for several minutes and immediately get medical assistance.
P302 + P352 If on skin, wash affected parts immediately with plenty of soap and water.

Danger
Eye Damage 1 H318 Causes serious eye damage

Danger
Skin Irritation 2 H315 Causes skin irritation
STOT SE 3 H335 May cause respiratory irritation

Supplemental Information
EUH210 Safety data sheet available on request.

Applying our Conservation Filler:

-Remove any loose material from the surface you are repairing.

-Using a spray bottle, lightly moisten the area with clean water.

-With a credit card or a flexible scraper, apply a thin layer to the desired area. Ensure there are no gaps.

-Once the filler is starting to dry, wipe of any excess with a sponge - producing a smooth and flush repair

-For repairs above 2mm, repeat this process by building layers until the damage is filled

Conservation Filler is Ideal For:

-Filling cracks up to 2 mm in one single application

-Stopping any gaps up to 5 mm with 2 - 3 applications

-Using on lime-based plasters

-Repairing gypsum, providing an almost invisible finish when repainted

Call 01469 531 227
Or 07743 362 408
limelincs@btinternet.com
www.lincolnshirelime.co.uk